

## TECHNICAL SPECIFICATION: PLAM DENSIFIER

### Sodium-based densifying treatment for internal concrete cementitious surfaces

In the presence of a new industrial or “cloudy” concrete floor (e.g. in Pavilux<sup>®</sup> or Deco Nuvolato<sup>®</sup> Isoplam<sup>®</sup>), but with at least 7 days of life, wash it with Isoplam<sup>®</sup> **Plam Apripori** acid and rinse thoroughly.

In the case of seasoned concrete without treatments, wash with Isoplam<sup>®</sup> **Plam Super Cleaner** degreaser and rinse thoroughly.

Application of Isoplam<sup>®</sup> **Plam Densifier**, at a rate of approx. 0.2-0.3 L/m<sup>2</sup>, rubbing with Isoplam<sup>®</sup> **white sponge disc** applied to the Isoplam<sup>®</sup> **Power trowel Machine**, keeping the surface wet and continuing to massage for at least 30 minutes.

Thorough rinsing of the surface with a pressure washer or Isoplam<sup>®</sup> **scrubber dryer** and subsequent complete removal of the water with Isoplam<sup>®</sup> **Professional squeegee**.

Application of one coat of Isoplam<sup>®</sup> **Antiolio Oil Repellent** (approx. 0.1 L/m<sup>2</sup>), Isoplam<sup>®</sup> **Metallic Wax** (0.03 L/m<sup>2</sup>) or Isoplam<sup>®</sup> **Plam Poly Wax** (0.03 L/m<sup>2</sup>).

The price includes: the protection of parts not affected by the processing, the supply and transportation of materials to the construction site, the equipment and machinery for carrying out the work.

**For a total of. .... m<sup>2</sup> at the price of € ...../m<sup>2</sup>**

#### Isoplam S.r.l.

Via E. Mattei 4 - 31010 Maser (TV) Italy  
Tel: +39 0423 925023 - Mail: info@isoplam.it  
Pec: isoplamsrl@pec.it - Web: www.isoplam.it

Reg. Imp. / Partita IVA IT02432450266 | R.E.A. n. TV-210216 | Cap. Soc. 12.000,00 i.v.  
Iscritta c.c.i.a.a. 02432450266 di Treviso in data 19.02.1996  
Società soggetta all'attività di direzione e coordinamento di MDF Holding