

TECHNICAL SPECIFICATION: PLAM DENSIFIER PLUS

Lithium-based densifying treatment for internal concrete cementitious surfaces

In the presence of a new industrial or “cloudy” concrete floor (e.g. in Pavilux[®] or Deco Nuvolato[®] Isoplam[®]) seasoned and without treatments, wash with Isoplam[®] **Plam Super Cleaner** degreaser and Isoplam[®] **Black Disc** mounted on the Isoplam[®] **Power trowel machine**, and thorough rinsing.

After complete drying, apply at least 2 coats of Isoplam[®] **Plam Densifier Plus**, at a rate of about 0.04 L/m² per coat, with Isoplam[®] **Wax Spreader** and going over between one coat and the other with Isoplam[®] **Polishing Machine** with Isoplam[®] **green twister disc** mounted.

The price includes: the protection of parts not affected by the processing, the supply and transportation of materials to the construction site, the equipment and machinery for carrying out the work.

For a total of. m² at the price of €/m²

Isoplam S.r.l.

Via E. Mattei 4 - 31010 Maser (TV) Italy
Tel: +39 0423 925023 - Mail: info@isoplam.it
Pec: isoplamsrl@pec.it - Web: www.isoplam.it

Reg. Imp. / Partita IVA IT02432450266 | R.E.A. n. TV-210216 | Cap. Soc. 12.000,00 i.v.
Iscritta c.c.i.a.a. 02432450266 di Treviso in data 19.02.1996
Società soggetta all'attività di direzione e coordinamento di MDF Holding