



SOLVENT RALI

Thinner for Plam Pool resin

DESCRIPTION

Solvent Rali Isoplam® is a diluent specially formulated for diluting the waterproofing resin Plam Pool Isoplam® and a solvent for cleaning the equipment used for its application.

USE

Solvent Rali Isoplam® is ready to use.

Use as a diluent: Solvent Rali must be incorporated and mixed in the mixture of the two components of Plam Pool up to a maximum of 25% of the total. Pay attention that the use of Solvent Rali in the Plam Pool reduces the waterproofing capacity of the latter.

Use as a solvent: remove the still fresh resin by immersing the equipment to be cleaned in Solvent Rali or by wiping with a cloth in natural fibers soaked in the product. Product residues must be disposed of in accordance with current regulations.

TECHNICAL FEATURES

| Appearance | Transparent liquid |
|----------------------------|------------------------|
| Odour | Characteristic |
| Relative density | 0,88 Kg/Lt |
| Flash point | 23 • T • 60 °C |
| Self-ignition temperature | 400°C |
| VOC (Directive 2010/75/CE) | 100,00 % - 880,00 g/Lt |
| VOC (volatile carbon) | 61,98 % - 545,45 g/Lt |

PACKAGING

Solvent Rali Isoplam® is supplied in 5 Lt cans.

STORAGE AND SAFETY

Keep only in the original container. Keep the containers closed, in a well-ventilated place, away from direct sunlight. Store in a cool and well-ventilated place, away from heat sources, open flames, sparks and other sources of ignition. The product is flammable.

If properly stored, the product is guaranteed for 24 months in the original packaging.

The packaging date is shown on the package (the lot number indicates, in sequence, year/week/day). Consult the safety data sheet before use. The product is intended for professional use only.

IMPORTANT:

All the information contained in this sheet is based on the best practical and laboratory experiences. It is the customer's responsibility to verify that the product is suitable for the intended use. Isoplam Srl declines all responsibility for the results of incorrect applications. It is always advisable to carry out tests on small surfaces before application. This sheet replaces and cancels the previous ones. The data can be changed at any time.

We also remind you that Isoplam products are intended for professional use and that Isoplam provides periodic training for its customers who request it. Anyone who uses these products without being enabled does so at their own risk.

1